



Poles	Dimension In. (mm)	
	A	B
2	3.96	8.04
3	7.92	12.10
4	11.88	15.96
5	15.84	20.00
6	19.80	23.90
7	23.76	27.90
8	27.72	31.92
9	31.68	35.88
10	35.64	39.84
11	39.60	43.74
12	43.56	47.74
13	47.52	51.70
14	51.48	55.66

REV	ECN. NO.	APP	DATE
A	EDIÇÃO INICIAL		

SPECIFICATION

Voltage Rating: 250V AC/DC

Current Rating: 5A AC/DC

Temperature Range: -25 ° C ~+85 ° C

Contact Resistance: 10 Milliohms Max.

Insulation Resistance: 1,000 Megohms Min.

Dielectric Withstanding Voltage: 1,500V AC/DC/Minute.

Material: Nylon 66, UL94V-0

Color: White

HOW TO ORDER: MX-3966-H-[]P-[]

1- N° of Contact
2 to 14
2- (R) RoHS Compliant

 MATRIX TECNOLOGIA IND. E COM. LTDA.			
UNIT mm	SCALE	TITLE	DATE SEPTEMBER 2007
TOLERANCE: ±0.25		3,96mm HOUSING	APP. BY
		MATL	CHK. BY
		DWG. NO.	DR. BY DINO