

| REV | ECN. NO. | APP | DATE |
|-----|----------------|-----|------|
| A | EDIÇÃO INICIAL | | |
| B | NOVO CÓDIGO | | |
| | | | |
| | | | |

Electrical Characteristics

Current Rating: 1.0 Amp. Max..

Dielectric Withstand Voltage:

800V AC RMS for 60Seconds.

Insulation Resistance:

1000M Ohms Min. at 500V DC.

HOW TO ORDER: 3020[S][][]DR 1 2 3

1- Version:

(S)-180°

2- N° of Ways:

See Table

3- Terminal Plating:

(D)-FLASH Au

(F)-0,38um Au

(G)-0,76um Au

(C)-0,38um Au/Sn

(H)-0,76um Au/Sn

| Pos. | Dimension | | | Pos. | Dimension | | |
|------|-----------|-------|-------|------|-----------|-------|-------|
| | A | B | C | | A | B | C |
| 06 | 13.20 | 12.10 | 4.00 | 28 | 35.20 | 34.10 | 26.00 |
| 08 | 15.20 | 14.10 | 6.00 | 30 | 37.20 | 36.10 | 28.00 |
| 10 | 17.20 | 16.10 | 8.00 | 32 | 39.20 | 38.10 | 30.00 |
| 12 | 19.20 | 18.10 | 10.00 | 34 | 41.20 | 40.10 | 32.00 |
| 14 | 21.20 | 20.10 | 12.00 | 36 | 43.20 | 42.10 | 34.00 |
| 16 | 23.20 | 22.10 | 14.00 | 40 | 47.20 | 46.10 | 38.00 |
| 18 | 25.20 | 24.10 | 16.00 | 44 | 51.20 | 50.10 | 42.00 |
| 20 | 27.20 | 26.10 | 18.00 | 50 | 57.20 | 56.10 | 48.00 |
| 22 | 29.20 | 28.10 | 20.00 | 60 | 67.20 | 66.10 | 58.00 |
| 24 | 31.20 | 30.10 | 22.00 | 64 | 71.20 | 70.10 | 62.00 |
| 26 | 33.20 | 32.10 | 24.00 | 68 | 75.20 | 74.10 | 66.00 |



MATRIX TECNOLOGIA IND. E COM. LTDA.

UNIT
mm

SCALE


TITLE

DATE DECEMBER 2009

TOLERANCE: ±0.25

BOX HEADER 2,00mm
PROFILE 5,6mm SMT

APP. BY



MATL

CHK. BY

DWG. NO.

DR. BY Felipe