

REV	ECN. NO.	APP	DATE
A	EDIÇÃO INICIAL		

Electrical Characteristics

Current Rating: 1.0 Amp. Max..



Dielectric Withstand Voltage:
800V AC RMS for 60Seconds.

Insulation Resistance:
1000M Ohms Min. at 500V DC.

Dimensions			
Pos.	A	B	C
08	10.65	8.85	6.00
10	12.65	10.85	8.00
12	14.65	12.85	10.00
14	16.65	14.85	12.00
16	18.65	16.85	14.00
20	22.65	20.85	18.00
22	24.65	22.85	20.00
24	26.65	24.85	22.00
26	28.65	26.85	24.00
30	32.65	30.85	28.00
34	36.65	34.85	32.00
40	42.65	40.85	38.00
44	46.65	44.85	42.00
50	52.65	50.85	48.00

HOW TO ORDER:
MX-3020-[S]-[]-[]-P6,4-[]
1 2 3 4

- 1- Version:
 (S)-180°
 (R)-90°
 2- N° of Ways:
 See Table
- 3- Terminal Plating:
 (D)-FLASH Au
 (F)-0,38um Au
 (G)-0,76um Au
 (C)-0,38um Au/Sn
 (H)-0,76um Au/Sn
 4- (R)-RoHS Compliant

 MATRIX TECNOLOGIA IND. E COM. LTDA.			
UNIT mm	SCALE	TITLE BOX HEADER 2,00mm PROFILE 6,4mm 180°	DATE SEPTEMBER 2007
TOLERANCE: ±0.25			APP. BY
		MATL	CHK. BY
DWG. NO.			DR. BY DINO