



REV	ECN. NO.	APP	DATE
A	EDIÇÃO INICIAL		

Specification:  
 Current rating: 1 A Max.  
 Dielectric withstanding voltage: 750 V(ac) for 1 min.  
 Contact resistance: 30 mΩ Max.  
 Insulation resistance: 1000 MΩ Min.  
 Total mating force: 9.0 Kgf Max.  
 Total unmating force: 1.0 Kgf Min.  
 Temperature range: -55°C~85°C

NO.	A±0.2	B±0.2	C±0.2	F±0.2
14	43.92	35.99	25.2	29.0
24	54.71	46.79	36.0	39.8
36	67.69	59.74	48.9	53.0
50	82.78	74.85	64.0	68.1

**HOW TO ORDER:**  
**MX-CEN-[ ]-[F]-S-[ ]**  
 1 2 3

- 1- N° of Contacts:  
14, 24, 36, 50
- 2- Contact Type:  
(M)-Male  
(F)-Female
- 3- (R)-RoHS Compliant

 <b>MATRIX TECNOLOGIA IND. E COM. LTDA.</b>			
UNIT mm	SCALE	TITLE CENTRONIC SOLDER TYPE FEMALE	DATE SEPTEMBER 2007
TOLERANCE: ±0.25			APP. BY
		MATL	CHK. BY
DWG. NO.			DR. BY DINO

