



REV	ECN. NO.	APP	DATE
A	EDIÇÃO INICIAL		

SPECIFICATIONS

- Electrical**
 Current Rating: 1 Amp
 Contact Resistance: 30 mΩ max.
 Insulation Resistance: 3000 MΩ min.
 Dielectric Withstanding Voltage: 500V AC for 1 minute
 Operating Temperature: -40°C to +105°C

HOW TO ORDER:
EDGE-[]-IDC-[]-[SR]-[]-[]
1 2 3 4 5

- 1- Nr. of Ways
See Table
- 2- Insulator Option:
(E)-With Mounting Ear
(F)-With Fork Mounting Ear
- 3- Function:
(SR)-With Strain Relief
()-Without Strain Relief
- 4- Terminal Plating:
(E)-Sn
(D)-FLASH Au
(F)-0,38um Au
(G)-0,76um Au
(C)-0,38um Au/Sn
(H)-0,76um Au/Sn
5-(R) RoHS Compliant

POSITION	A	B	C	D
10	43.06	10.16	38.06	22.36
14	48.14	15.24	43.14	27.44
16	50.68	17.78	45.68	29.98
20	55.76	22.86	50.76	35.06
26	63.38	30.48	58.38	42.68
34	73.54	40.64	68.54	52.84
40	81.16	48.26	76.16	60.46
50	93.86	60.96	88.86	73.16
60	106.56	73.66	101.56	85.86
62	109.10	76.20	104.10	88.40
64	111.64	78.74	106.64	90.94

		MATRIX Tecnologia Ind. e Com. Ltda.	
UNIT mm	SCALE	TITLE CARD EDGE 2,54mm IDC TYPE WITH EAR	DATE September 2007
TOLERANCE: ±0.25			APP. BY
		MATL	CHK. BY
		DWG. NO.	DR. BY DINO