




REV	ECN. NO.	APP	DATE
A	EDIÇÃO INICIAL		
B	NOVO CÓDIGO		



Unit: mm; Tolerances: ± 0.15 mm
Reference dimension for PCB layout

TECHNICAL CHARACTERISTICS

1. General Characteristics

Dimension: 56.20L x 40.00W x 6.80H mm

Weight: Approx. 7.56 g

Contact principle: Friction technology

Operating position: Shaft up / Down / Horizontal

Mounting System: Thru-Hole with Snap-in-lock

Durability: 200,000 cycles

2. Mechanical Characteristics

Insulation material: Thermoplastic, UL 94V-0

RoHS Directive 2002/95/EC Compliant

3. Electrical Characteristics

Number of contacts: 8 pins

Contact resistance: 50 m Ω typical, 100 m Ω max.

Insulation resistance: >1000 M Ω / 500 VDC

Switch type: Blade

Operation: Normally Open

4. Solderability

Wave: 260°C, 5 sec.

IR reflow: Not applicable

Manual soldering: 360°C, 3 sec. Max.

5. Environmental Characteristics

Operating temperature: - 40°C ~ + 85°C

Operating humidity: 10 % ~ 95 % RH

Storage temperature: - 40°C ~ + 85°C

Storage humidity: 10 % ~ 95 % RH

HOW TO ORDER: ICA6068CTHR



MATRIX TECNOLOGIA IND. E COM. LTDA.

UNIT	SCALE	TITLE	DATE
mm		ICA6068CTHR	MARCH 2010
TOLERANCE: ± 0.25			APP. BY
		MATL	CHK. BY
		DWG. NO.	DR. BY FELIPE